

LAVAL SYSTEMS LIGHTING OPTIONS

LIGHTING OPTIONS

TriLight
LumiCAM
CamLight



TRILIGHT SPECIFICATIONS

- Three military-grade dive lights
- Pressure rated to 1,300 feet (396.2 m) of submergence
- Powered via easily accessible AA batteries
- Four high intensity Nichia LEDs in each light
- 20 hours of light
- Lamp life of 10,000+ hours
- 38 lumens per light
- Mounted by adjustable stainless steel collar
- Removable rubber glare guard to focus the beam
- Limited Lifetime Warranty

LUMICAM SPECIFICATIONS

Housing: Electro-polished stainless steel
Diameter: 5.65 inches (14.4 cm)
Length: 13.85 inches (35.2 cm)
Weight: 34 lbs (15.4 kg)
Lens: Sapphire
Depth Rating: 5,000 feet (1,524 m)
Power Requirement: Operates from standard Laval control unit.

CAMLIGHT SPECIFICATIONS

- Adjustable Extension Bar
- View Boreholes up to 30 inches
- Operates to Depths of 5,000 feet
- Easily Adapts to Laval Camera
- Durable Quartz Lamp Cover will not Discolor or Fracture
- Easily Removable
- Low Voltage Lamp for Extended Life Expectancy to 2,000 hours

Lamp: 24 Volt Quartz Halogen


Output: 1,350 Lumens

Lamp Cover: Quartz

Light Bar: Extendable from 8 to 18 inches

Depth Rating: 2,500 psi (5,000 feet of submergence)

Life Span: 2,000 Hours



Note: Specifications subject to change. Confirm when ordering.

60 years of innovation

www.lavalunderground.com

2476 North Bundy Drive | Fresno, CA 93727, USA

Telephone: (559) 251-1396 | Fax: (559) 251-2096 | Email: info@lavalunderground.com